



ExionLC™ AD Multiplate Autosampler Specifications

An ideal replacement for the standard ExionLC AD Autosampler, the Multiplate Autosampler expands sample capacity over threefold without need for a separate Rack Changer. Three drawers can be configured to accept 6 regular or deep-well microtiterplates (MTP) in either 96 or 384-well formats. With the optional vial trays, the ExionLC AD Multiplate Autosampler can hold up to 324 x 1.5 mL vials.

ITEM	SPECIFICATION
Injection method	Variable injection volume flow through design (no sample loss during injection)
Injection volume setting range	0.1 to 50 μ L (0.1 to 0.9 μ L in 0.1 μ L increments, 1 to 50 μ L in 1 μ L increments) 1 to 2000 μ L (with optional Large Volume Injection sample loop)
Injection volume setting range	<ul style="list-style-type: none"> • With 96-well microtiter plate: 576 • With 384-well microtiter plate: 2304 • With 1.5 mL vials: 324 (requires 54 vial adapter plate)
Injection volume precision	RSD \leq 1.0% (0.5 to 0.9 μ L), RSD \leq 0.5% (1.0 to 1.9 μ L) RSD \leq 0.25% (2.0 to 4.9 μ L), RSD \leq 0.2% (5.0 to 50 μ L)
Injection volume accuracy	\pm 1% (at 50 μ L injection, n = 10)
Carryover	0.0015% max. (under specified conditions)
Sample aspiration rate	0.1 to 15 μ L/sec. (0.1 μ L/sec. increments)
Rinse aspiration rate	variable (1 to 35 μ L/sec., 1 μ L/increments)
Injection cycle time	14 seconds (under specified conditions)
Internal rinsing	Before and/or after sample injection, needle external and/or internal rinsing, four rinse solutions maximum available
Maximum pressure	1300 bar
Sample cooling system	Direct cooling system (environment conditions: room temperature below 30°C with humidity less than 70% when cooler temperature is set to 4°C), dehumidification function included.
Cooling range settings	4 to 40°C (under specified conditions)
Temperature accuracy	\pm 6°C (not possible to cool to 1°C or below)
Liquid contact part materials	Stainless steel (SUS316L, SUS316), ceramic, PTFE, ETFE, FEP, GFP, sapphire, PEEK, Polyimide
ENVIRONMENTAL	
Working temperature	4°C to 35°C
Relative humidity	20-85%
Dimensions (w x h x d)	540 x 415 x 500 mm
Weight	61 kg
ELECTRICAL	
Power supply voltage	AC100 V to 240 V
Power consumption	550 VA
Rated breaking capacity	75A
Power supply frequency	50/60 Hz

ITEM	SPECIFICATION
SAFETY	
Safety and EMC compatibility	ICES-001 Class B CE (EN61010-1, EN61326-1, EN55011 Class B) FCC Pt 15 Class B CAN/CSA-C22.2 No. 61010-01 UL std. No. 61010-1
Installation environment	Installation category II Pollution degree 2 Altitude 2000 m or lower Indoor installation

AB Sciex is doing business as SCIEX.

© 2015 AB Sciex. For research use only. Not for use in diagnostic procedures. The trademarks mentioned herein are the property of the AB Sciex Pte. Ltd. or their respective owners.
AB SCIEX™ is being used under license.

RUO-MKT-07-2216-A 06/2015



Headquarters

500 Old Connecticut Path, Framingham, MA 01701, USA
Phone 508-383-7800
www.sciex.com

International Sales

For our office locations please call the division
headquarters or refer to our website at
www.sciex.com/offices