

# Microwave Chemistry with Non-polar Reaction Solutions



## Introduction

Microwave heating has been a versatile and powerful tool for synthetic chemists since the 1980s, advancing nanomaterial assembly, drug discovery, peptide synthesis, and more.<sup>1-4</sup> The two mechanisms by which microwaves generate heat, ionic conduction and dipolar rotation, rely on an ion or molecule's ability to align itself with the ever-oscillating electric field of a microwave.<sup>5</sup> In general, highly polarized species undergo ionic conduction and dipolar rotation most readily, while low-polarity species are slowest to heat.


A common measure of polarity is the dielectric constant ( $\epsilon'$ ), which measures a compound's ability to store electrical charges. Though useful, this value can sometimes contradict another important dielectric parameter, the dielectric loss constant ( $\epsilon''$ ), which measures a solvent's ability to dissipate absorbed microwave energy to its surroundings. In microwave heating, the dielectric loss constant ( $\epsilon''$ ) provides the best gauge of a material's ability to efficiently absorb microwaves and undergo heating. Typically, high-absorbing materials have an  $\epsilon'$  greater than 14, while low-absorbing solvents have an  $\epsilon''$  less than 1 (Table 1).<sup>5</sup>

A common misconception regarding microwave heating, however, is that microwaves can benefit only experiments employing polar solvent systems. The advantages of microwave heating can be harnessed despite the dielectric characteristics of a solvent; most reactions involve polar and/or ionic species that can interact directly and instantaneously with microwave energy, even if the solvent does not absorb effectively.

To demonstrate the efficacy of microwave heating in transformations employing low-polarity solvents, the simple modification and optimization of a Diels-Alder reaction in toluene (Scheme 1) was adapted from an established protocol employing water.<sup>6</sup> This common cycloaddition is favored for its ability to produce ring structures and two new carbon-carbon bonds.

**Table 1:** The Dielectric Constants and Dielectric Loss Constants of Six Common Solvents<sup>5</sup>

Solvent	Dielectric Constant ( $\epsilon'$ )	Dielectric Loss Constant ( $\epsilon''$ )
DMSO	45.0	37.125
Water	80.4	9.889
Acetonitrile	37.5	2.325
DCM	9.1	0.382
Toluene	2.4	0.096
Hexanes	1.9	0.038



**Scheme 1:** Microwave-Heated Diels-Alder Reaction in Toluene

## Materials and Methods

### Reagents

Toluene was obtained from VWR (Radnor, PA). Maleimide and 2,3-dimethyl-1,3-butadiene were obtained from TCI Chemicals (Tokyo, Japan).

### Procedure

A 10 mL vessel, equipped with stir bar, was charged with maleimide (1.0 equiv.), 2,3-dimethyl-1,3-butadiene (2.0 equiv.), and solvent (2.5 – 4.95 mL). Then, the vial was sealed with a Teflon-lined silicon cap and placed in the Discover® 2.0 microwave cavity. The reaction mixture was heated to a specified temperature for an indicated period of time. Then, the solution was cooled to room temperature and analyzed via thin layer chromatography. The crude yield was obtained through rotary evaporation of the reaction mixture.

## Results

To start, experimental conditions from the literature-established<sup>6</sup> microwave-assisted Diels-Alder reaction were tested; heating maleimide and 2,3-dimethyl-1,3-butadiene at 110 °C for 5 min in water resulted in a 94% yield, consistent with reported values (**Table 2**, entry 1). Employing toluene with otherwise identical reaction conditions did not affect experimental outcome; a comparable yield of 96% was observed (**Table 2**, entry 2).

From this point, the efficacy of microwave heating with toluene was further investigated; a series of experiments with diminishing reaction concentration was studied (and optimized). Diluting reaction concentration to 0.20 mM (maleimide), one

tenth of the original concentration, did not result in quantitative conversion to product after 5 min, at 110 °C (**Table 2**, entry 3). A simple temperature optimization to 120 °C secured complete conversion and satisfactory yield (**Table 2**, entry 4).

Following this adjustment, an experiment where the reaction concentration was decreased by an additional 50% and then heated at 120 °C for 5 min was performed; again, incomplete conversion to product was observed (**Table 2**, entry 5) due to the low concentration of reactants. To restore quantitative conversion this time, an increase in both temperature and time was implemented; heating the solution at 130 °C for 10 min afforded the desired product in 97% yield (**Table 2**, entry 6).

A final dilution of reaction concentration to 0.050 mM (maleimide) resulted in incomplete conversion when heated under the previous conditions (**Table 2**, entry 7); extending reaction time by 5 min, however, restored quantitative conversion (**Table 2**, entry 8).

## Conclusion

The efficacy of microwave heating in transformations employing low-polarity solvents was demonstrated through the simple modification and optimization of a Diels-Alder reaction. Though originally performed in a moderately polar solvent (water)<sup>6</sup>, the microwave heating of maleimide and 2,3-dimethyl-1,3-butadiene in low-polarity toluene yielded identical results. Even when diluted nearly 40-fold, quantitative conversion to product was achieved. Due to the microwave-absorbing properties of polar reactants typical of synthetic transformations, microwave heating is a simple and effective technology in the practice of all types of synthetic chemistry, despite the dielectric characteristics of the solvent in use.

**Table 2:** Optimization of Diminishing-Concentration Diels-Alder Reactions in Toluene

Entry	Maleimide (mM)	Diene (mM)	Solvent	Temperature (°C)	Time (min)	Yield (%)
1	1.95	3.90	Water	110	5	94
2	1.95	3.90	Toluene	110	5	96
3	0.20	0.40	Toluene	110	5	Incomplete conversion
4	0.20	0.40	Toluene	120	5	93
5	0.10	0.20	Toluene	120	5	Incomplete conversion
6	0.10	0.20	Toluene	130	10	97
7	0.050	0.10	Toluene	130	10	Incomplete conversion
8	0.050	0.10	Toluene	130	15	95

## References

1. Tierney, J.P.; Lidstrom, P. *Microwave Assisted Organic Synthesis*, CRC Press: Boca Raton, FL, 2005, p 2.
2. Zhu, Y.-J.; Chen, F. *Chem. Rev.* **2014**, *114*, 6462–6555.
3. Larhed, M.; Hallberg, A. *Drug Disc. Today* **2001**, *6*, 406–416.
4. Jacob, J. *Int. J. of Chem.* **2012**, *4*, 1.
5. Hayes, B. L. *Microwave synthesis: chemistry at the speed of light*; CEM Publishing: Matthews, NC, 2002, pp 3-5.
6. Leadbeater, N. E.; McGowan, C. C. *Clean, Fast Organic Chemistry: Microwave-assisted laboratory experiments*; CEM Publishing: Matthews, NC, 2006, pp 60-61.

---

**United States  
(Headquarters)**

800-726-3331  
704-821-7015  
info@cem.com

**France**

33 (01) 69 35 57 80  
info.fr@cem.com

**Germany, Austria,  
Switzerland**

(49) 2842-9644-0  
info@cem.de

**Ireland**

+353 (0) 1 885 1752  
info.ireland@cem.com

**Italy**

(39) 35-896224  
info.srl@cem.com

**Japan**

+81-3-5793-8542  
info@cemjapan.co.jp

**United Kingdom**

(44) 1280-822873  
info.uk@cem.com

**[www.cem.com](http://www.cem.com)**

© 2020 CEM Corporation  
All rights reserved. This may not be  
reproduced or published without  
written permission from CEM.